

38305

LEVEL TECH

BY



**2000-2010 CHEVY/GMC 1500HD/2500HD/3500 HD
2WD / 4WD P/U 8-Lug 3/4 Ton & SUVs with Torsion Bars**

2.5" TORSION KEY KIT

KIT INCLUDES:

- 2) 2000-2010 HD Torsion Keys
- 2) Front Lower Shock Bkts



1) Prior to lifting the vehicle it is recommended that you measure the stock height so that you have a base line measurement. Measure from the bottom of the wheel to the lip of the fender.

Disassembly

2) With the vehicle on level ground and set the emergency brake and block the rear tires. Disconnect the negative battery cable from the battery (Note that some vehicles have 2 or more batteries you will need to disconnect the negative cables from all batteries). Jack up the front end of the truck and support the frame rails with jack stands.

NEVER WORK UNDER AN UNSUPPORTED VEHICLE

3) Remove the front wheels and tires.

4) Remove front lower shock mount bolt save the hardware.

5) Remove the front lower shock bracket from the lower control arms and set aside.

6) Locate the torsion key cross member under the cab of the truck. Using a GM Torsion Bar Unloading Tool compress the driver's side key so that you can remove the threaded part of the torsion adjuster. Remove the torsion key adjusting bolt and adjuster completely. Releasing the tension on the unloading tool will now release the tension on the torsion bar. Slide torsion bar forward allowing the torsion key to be removed.


7) Mark torsion bars indicating driver and passenger.

(NOTE- Do not attempt to unload or remove torsion bars without the proper torsion bar tool. Torsion Bars are under extreme tension)

Assembly

- 8) Install the FULL THROTTLE SUSPENSION Billet Steel torsion key and slide torsion bar back into position. Apply pressure with torsion bar unloading tool to the torsion key, and create enough space to reinsert the torsion key keeper that the adjusting bolt threads into. **IMPORTANT!** Make sure the Torsion Bar is extended at least $\frac{1}{4}$ " through the Torsion Key.
- 9) Reinstall the factory adjusting bolt, and adjust it so $\frac{1}{4}$ " of bolt threads extend beyond torsion key keeper. **IMPORTANT!** – Each $\frac{1}{4}$ " of adjustment on the bolt equals 1" at the wheel. It is best to check ride height after this initial setting and adjust as needed. Note: Over Cranking of the suspension will affect ride quality and is not recommended.
- 10) Install the FTS Shock brackets onto the stock location with the taller side toward the frame, reinstall the factory hardware into the arm and tighten to 50 lb.-ft. Now install the shock back into the new FTS shock bracket and Torque to 100 lb.-ft. See pic below.
- 11) Repeat steps 1 through 10 on the Opposite Side of the vehicle. Follow each step closely making sure to double-check the torque on all fasteners. Measure the distance between the tires and fenders to make sure both sides of the truck are even.
- 12) Reinstall tires and torque lugs to factory specs.
- 13) Wheel Alignment a Certified Alignment Technician that is experienced with lifted vehicles is recommended to perform the alignment. *Minor trimming of the front air dam may be required to ensure adequate tire clearance.*It is also recommended that you adjust your headlights whenever your vehicle's ride height is altered.

THANK YOU FOR USING FULL THROTTLE SUSPENSION LEVELING KITS





Product Warranty and Warnings-

FTS provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following FTS items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Warranty.

FTS does not warrant any product for finish, alterations, modifications and/or installation contrary to FTS instructions. Alterations to the finish of the parts including but not limited to painting, powder coating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

FTS products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America. Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. FTS makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturer's production changes and/or inconsistencies by the auto manufacturer, FTS cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in FTS's catalog are only a guideline for street driving with noted fender trimming. FTS is not responsible for damages to the vehicle's body or tires.

FTS's obligation under this warranty is limited to the repair or replacement, at FTS option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. FTS is not responsible for damages and/or warranty of other vehicle parts related or non-related to the installed FTS product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by FTS.

FTS suspension components must be installed as a complete system including shocks as shown on our current website. All warranties will become void if FTS parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. FTS does not warrant products not manufactured by FTS.

Installation of FTS product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of FTS products with the consumer prior to purchase.

FTS reserves the right to supersede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. FTS is not responsible for misprints or typographical errors within the catalog or price sheet.

Thank You for choosing Full Throttle Suspension
Tech support 559-271-8685 or send email to fts.dwgs@gmail.com