

65855



2014-2015 DODGE 2500 4WD 6" BASIC KIT W/ FRONT COIL SPRINGS



65855

2014-2015 Dodge 2500 6" Basic Kit W/ Front Coil Springs

66855-3 Component Box 1

- 1) 6" Left Radius Arm Drop Brackets
- 1) 6" Right Radius Arm Drop Brackets
- 1) Track Bar Drop Bracket
- 1) Left Sway Bar Drops
- 1) Right Sway Bar Drops
- 1) Transmission Mount

Hardware Bag 1

- 1) Pitman Arm Sleeve
- 1) 1.375 Hardened Washer
- 3) 1/2" X 1 1/2" Bolts
- 3) 1/2" Nut Inserts
- 3) 1/2" Washers
- 1) 18mm X 90mm Bolts
- 1) 18mm Nylock Nuts
- 2) 18mm Washers
- 5) 7/16" X 1 1/4" Bolt
- 5) 7/16" Nylock Nut
- 9) 7/16" Washers
- 1) 7/16" Long Nut Wedge

Hardware Bag 2

- 8) 1/2" x 1 1/2" Bolts
- 8) 1/2" Nut Inserts
- 8) 1/2" Washers
- 2) 18mm x 130mm Bolts
- 2) 18mm Nylock Nuts
- 4) 18mm Washers

Hardware Bag 3

- 1) BL307 Left Brake Line Bracket
- 1) BL308 Right Brake Line Bracket
- 1) BL420 Rear Brake Line Bracket
- 1) 5/16" x 1" Bolts
- 1) 5/16" Nylock Nuts
- 6) 5/16" Washers

66855-10 6" Coil Springs

- 2) 6" Front Coil Springs

65854-2 Component Box 2

- 1) Track Bar Bracket
- 2) 3 1/2" Coil Spacers
- 2) 3 1/2" Sway Bar Drop Bracket
- 2) 3 1/2" Rear Bump Stops

Hardware Bag 1

- 1) S2842 Sleeve .565 x 1.0 x 2.150 Sleeves
- 1) 9/16" x 4" Bolt
- 1) 9/16" Nylock Nut
- 2) 9/16" Washers
- 9) 7/16" x 1 1/4" Bolt
- 1) 7/16" x 1 1/2" Bolt
- 10) 7/16" Nylock Nut
- 20) 7/16" Washers
- 2) 1/2" x 1 1/2" Bolts
- 2) 1/2" Nylock Nuts
- 4) 1/2" Washers
- 6) 3/8" x 1" Bolts
- 6) 3/8" Nylock
- 12) 3/8" Washers


1) Disconnect the negative terminal on the battery. Jack up the front end of the truck and support the frame rails with jack stands. **NEVER WORK UNDER AN UNSUPPORTED VEHICLE!** Remove the front tires.

2) Support the front axle with 2 floor jacks.


3) Remove the bolts attaching the brake line tabs to the front axle.



4) Remove the front sway bar end links from the axle mount. Remove the bolts securing the sway bar mounts to the frame and set the sway bar aside, save all sway bar hardware. **NOTE** the orientation of the sway bar for reinstallation.



5) Disconnect the front 4wd actuator from the axle housing.



6) Remove bolt holding the drive shaft to the front differential.



7) Disconnect the ABS wiring.

8) Using a crescent wrench loosen the jam nuts on the drag link.



9) Remove the hardware attaching the drag link to the pitman arm. Save the hardware.



10) Using a hammer, strike the pitman arm to dislodge the tie rod from the pitman arm.




11) Unscrew the tie rod end out of the coupler.



12) Using a die grinder or abrasive saw remove the flat portion of the tie rod.




13) Remove the bolt securing the track bar to the frame and separate. Save the track bar hardware.





14) Remove the front upper nut and the lower bolts securing the shock to the axle. Save the lower Hardware. Remove shocks.



15) Leaving the front axle supported on the 2 jacks raise the truck enough to remove the coil springs. Save the upper rubber insulator, coil springs & shocks for Reassembly. USE EXTREME CARE WHEN WORKING WITH COILS THAT ARE UNDER LOAD!

Skip step 16 if Installing FTS 2.0" Shocks.

16) Install front shock extenders.



17) Install the shocks back into the truck to allow the front axle to hang from.



18) Loosen the bolts securing the link arms to the frame.




19) Remove the bolts attaching the link arms to frame.



20) Install the FTS radius arm drop bracket using the factory hardware.



21) Mark the hole on the bottom side of the frame.



22) Mark the 3 holes on the side of the frame with a center punch.



23) Drill all 4 frame holes to 11/16".



24) With holes enlarged install nut inserts and tighten bolt till each nut insert crimps itself tight into the frame.




25) Use a 3/8" impact to tighten the nut-serts into the frame as shown.




26) Shown below is the 4 nut-serts installed.




27) Once all nut inserts are installed, re-install the bracket using 1/2" x 1 1/2" hardware.




28) Install the arm into the FTS drop bracket using the factory hardware.




29) Install the track bar bracket as shown, Use the factory hardware thru the factory hole in the frame. Snug the bolt enough to hold the bracket in place. Mark the 3 holes on the bottom side of the frame using the track bar bracket as a guide.




30) Remove bracket and drill hole to 11/16". Install the nut-serts as shown.




31) Reinstall bracket using the 18mm x 90mm hardware.




32) Install the 3 supplied $\frac{1}{2}$ " x $1\frac{1}{2}$ " bolts as shown below.



33) Install the nut tab using the $\frac{7}{16}$ " x $1\frac{1}{4}$ " hardware as shown below.



34) Track bar bracket installed.



35) With the front axle supported on the jack stand, remove the front shocks. Raise the vehicle enough to install the FTS coil springs as shown below. When installing the coil spring make sure to reinstall the factory insulator as shown.




36) Re-attach the upper and lower Shock Hardware.




37) Drill out the taper factory pitman arm using a 7/8" drill bit or reamer.



39) Install the tie rod into the pitman arm from the bottom side. Install supplied washer on top side of pitman arm as shown.




38) Note that the sleeve will be installed from the bottom of the pitman arm. Now reconnect the factory tie rod to the pitman arm making sure it now goes from the bottom facing up as shown in the picture. Install supplied hardened flat washer and factory nut. Torque the original nut to 45 ft.-lbs.



41) Install the sway bar brackets as shown using the factory hardware attaching the bracket to the frame.



42) Use the 7/16" x 1 1/4" hardware to attach the sway bar to the drop brackets.



43) Reconnect the sway bar end link to the axle using the factory hardware.





44) Reconnect the brake line bracket to the axle using the factory hardware as shown below

45) Reconnect the ABS wire removed in step 7.




46) Install the supplied DRIVER upper brake line drop bracket using the factory hardware to attach the bracket to the frame and the supplied 5/16" x 1" hardware to attach the bracket to the brake line hardline bracket.




47) Install the supplied PASSENGER upper brake line drop bracket using 5/16" x 1" hardware to attach the bracket to the frame and the supplied 5/16" x 1" hardware to attach the bracket to the brake line hardline bracket.



48) Support the transmission using a transmission jack or tri pod stand. Remove the transmission cross member.



49) Remove the stock transmission mount.






50) Reinstall the transmission mount into the truck using the factory hardware.



51) Reinstall the transmission cross member into the truck using the factory hardware.



52) Using a crescent wrench, tight the jam nuts on the steering drag link as shown below.



53) Install wheel and tires.


54) Rear suspension is all complete

Final Check

- 1) The vehicle will need a complete front end alignment.
- 2) Check all hardware after 500 miles.
- 3) Adjust headlights.

REAR INSTRUCTIONS:


- 1) Jack up the rear end of the vehicle and support the frame.
- 2) Remove the rear wheels.
- 3) Support the rear axle with a hydraulic jack.
- 4) Disconnect the rear brake line bracket from the axle, retain all hardware.




- 6) Disconnect the rear track bar from the axle, retain all hardware.




- 5) Disconnect the rear sway bar end links front the frame, retain all hardware.



- 8) Disconnect the rear shocks lower shock hardware.




9) Disconnect the rear shocks upper shock hardware.




10) Lower the rear axle slowly, Remove the rear coil springs and upper and lower coil spring retainers.




11) Install the rear sway bar end link drop brackets using the supplied hardware.




12) Drill the side hole in the frame 3/8". Use the sway bar drop bracket as the guide. Drill all the way through both sides.




13) Install the 3/8" x 1" hardware as shown below.




14) Enlarge the holes in the lower coil mounting plate to 7/16"




15) Install the track bar bracket using the supplied spacer as shown, Use the 5/8" x 4" hardware supplied, do not tighten at this time.



16) Install the supplied 7/16" hardware in the 2 lower holes as shown.




17) Install the DRIVER coil spacer using the 7/16" x 1 1/4" in the front hole and the 7/16" x 1 1/2" in the rear hole.



18) Tighten all the hardware attaching the track bar bracket and coil spacer to the axle.



19) Install the PASSENGER side coil spacer using the supplied 7/16" x 1 1/4" hardware as shown



20) Install the rear coil springs.




21) Install the rear shock extender or shock at this time.



22) Reattach the rear sway bar end links to the drop bracket using the factory hardware.




23) Install the rear bump stop bracket as shown.





24) Install rear brake line bracket as shown.





Product Warranty and Warnings-

FTS provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following FTS items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Reservoir shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

FTS does not warrant any product for finish, alterations, modifications and/or installation contrary to FTS instructions. Alterations to the finish of the parts including but not limited to painting, powder coating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

FTS products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death.

FTS makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconsistencies by the auto manufacturer,

FTS cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in FTS's catalog are only a guideline for street driving with noted fender trimming. FTS is not responsible for damages to the vehicle's body or tires.

FTS's obligation under this warranty is limited to the repair or replacement, at FTS option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. FTS is not responsible for damages and/or warranty of other vehicle parts related or non-related to the installed FTS product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by FTS.

FTS suspension components must be installed as a complete system including shocks as shown on our current website. All warranties will become void if FTS parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. FTS does not warrant products not manufactured by FTS.

Installation of FTS product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of FTS products with the consumer prior to purchase.

FTS reserves the right to supersede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. FTS is not responsible for misprints or typographical errors within the catalog or price sheet.

Thank You for choosing Full Throttle Suspension

Tech support 559-271-8685 or send email to fts.dwgs@gmail.com